



**Features:**

- Single high power COB LED
- High CRI, traditional color consistency.
- Proprietary optic
- Unrivaled thermal management
- Instant on/off
- Proprietary heat sink design
- Vibration and shock resistant
- No ballast required
- Constant current design
- Greater than 50% savings in energy
- No flickering, noiseless operation
- UL Listed
- 5 Year Warranty

# Specification Sheet

## 150W Equivalent Non Dimmable PAR38

**Specifications:**

Lumen Output:	2100 lm (Day White)
Wattage:	29 Watts
Kelvin:	(2700K) Warm White (3000K) Warm White (4100K) Natural White (5000K) Day White
CRI:	82 Typical
Dimensions:	4.8" x 5.3" (121.9mm x 134.6mm)
Light Distribution:	40°, 25°, 15°
LED Count:	1 High Power COB LED
Base:	E-27
Dimming:	No
Housing Temp:	Less than 95°F (35°C)
Max. Ambient Peak Temp:	-22°F to 104°F (-30°C to 40°C)
Replaces:	150 Watt Incandescent
Working Voltage:	120VAC
Frequency:	60HZ
Net Weight:	1.15 lbs (0.52 kg)
Life Cycle:	50,000 Hours

Attention: All specifications are subject to change without notice.

**Product SKU:**

- |                                 |                                 |
|---------------------------------|---------------------------------|
| • 18F-P38-29-27K-ND (2700K 40°) | • 18F-P38-29-41K-ND (4100K 25°) |
| • 18F-P38-29-30K-ND (3000K 40°) | • 18F-P38-29-50K-ND (5000K 25°) |
| • 18F-P38-29-41K-ND (4100K 40°) | • 18S-P38-29-27K-ND (2700K 15°) |
| • 18F-P38-29-50K-ND (5000K 40°) | • 18S-P38-29-30K-ND (3000K 15°) |
| • 18N-P38-29-27K-ND (2700K 25°) | • 18S-P38-29-41K-ND (4100K 15°) |
| • 18N-P38-29-30K-ND (3000K 25°) | • 18S-P38-29-50K-ND (5000K 15°) |



**50  
Thousand  
Hours**

**5  
YEAR  
WARRANTY**

**TITAN LED**  
"Changing the World One Socket at a Time"